

# Specification

Product Code	0409	0406	0402	0401
Model No.	PF50C	PF100C	PF150C	PF200C
Description	<b>Grinlites Orion</b> 50Watt Flood Light	<b>Grinlites Orion</b> 100Watt Flood Light	<b>Grinlites Orion</b> 150Watt Flood Light	<b>Grinlites Orion</b> 200Watt Flood Light
Wattage (W)	50	100	150	200
Luminous Flux (lm)	5560	11110	16670	22230
Input Voltage (V)	240 VAC			
Colour	Cool White			
CCT (K)	5000-6500			
Beam Angle (Degree)	70 x 120			
LED Ambient Temperature	<70°C			
Case Temperature	<60°C			

## Benefits and Features

- Energy saving up to 70%
- Reliable heat dissipation design provides low running temperature <60°C
- Long life span with a 60000 hour design life and a 3 year warranty (Return to supplier)
- State of the art design light structure to fit retrofit and new applications
- Adjustable mounting bracket fixture provides flexible installation options.
- IP67 Protection Rating



## Application

- Outdoor Lighting
- Industrial Lighting
- Retail Lighting
- Feature Lighting
- Car Park Lighting



 RoHS



## GrinLites LED Flood Light

AC Techart Electronics  
 4 Eton Court, Hallam, VIC 3803

PH 03 8759 0018 FAX 03 8774 2076 EMAIL: [admin@actechart.com.au](mailto:admin@actechart.com.au)