



product introduction

The Multi-Drive controller combines the Constant ON operation and the high pulse operation into one easy to use product. The Multi-Drive controller allows the user to run the product in Constant ON operation or pulse/strobe the light at the maximum allowed intensity by the LED manufacturer by simply setting the product parameters. The built-in Multi-Driver also protects the LEDs from premature degradation and failure caused by excessive heat by regulating the current delivered to the LEDs and limiting the duty cycle of the light. NPN or PNP signal input options, a 0-10V analog intensity control, and an industry standard M12 power cable allow for versatility and eases installation time.



product features



- Continuous Operation or OverDrive
- Sealed to IP65 standards
- Driver Built In – No External Wiring To A Driver
- NPN and PNP Signal Input Options
- Industry Standard 5-Pin M12 connector



Constant ON product specs

Electrical Input	24 VDC +/- 5%		
Current	750mA per 300mm (12")		
Wattage	18W per 300mm (12")		
ON/OFF Input	PNP ► +4VDC or greater to activate	NPN ► GND (<1VDC) to activate	5µS LED activation time
PNP Line	3.7mA @ 3VDC	6.2mA @ 5VDC	12.6mA @ 10VDC 30.4mA @ 24 VDC
NPN Line	22mA @ Common (0VDC)		
Continuous Mode	Light will be in continuous mode by leaving signal on NPN/PNP input active		
Connection	5 pin M12 connector		
Ambient Temperature	-40° - 50° C (-40° - 122° F)		
IP Rating	IP65		
IEC 62471 Rating	See page 4 for details		



OverDRIVE product specs

Electrical Input	24 VDC +/- 5%		
Current	5A during strobe per 300mm 500mA Max. Avg. per 300mm		
Wattage	120W during strobe per 300mm 12W Max. Avg. per 300mm		
Strobe Input	PNP ► +4VDC or greater to activate	NPN ► GND (<1VDC) to activate	5µS LED activation time
PNP Line	3.7mA @ 3VDC	6.2mA @ 5VDC	12.6mA @ 10VDC 30.4mA @ 24 VDC
NPN Line	22mA @ Common (0VDC)		
OverDrive Mode	Connect Pin 5 to GND (more info. in wiring configuration)		
Duty Cycle	Max. 10%		
Strobe Duration	Max. 125mS		
Connection	5 pin M12 connector		
Ambient Temperature	-40° - 50° C (-40° - 122° F)		
IP Rating	IP65		
IEC 62471 Rating	See page 4 for details		



product number key

LEXXX – XXX- X*

→ Part Number Key

Product Family:
Linear Light
LE Series

Length:
300mm

Color:
470- Blue
505 - Cyan
530- Green
625- Red
850/940- IR
WHI- White

Lenses:
L- Line
W - Wide

* Lights come standard with narrow lenses

CE and RoHS Compliant



warnings




Attention

Please note that the power requirements are 750mA per 300mm at 24VDC for constant ON operation and 5A per 300mm at 24VDC for strobe mode. Failure to supply light with 750mA for constant ON or 5A for strobe per 300mm may result in non-repeatable lighting. Contact Smart Vision Lights for more information.




wiring configuration

Wiring configuration for **CONSTANT ON** operation

	Pin	Function	Signal	Wire Color
	1	Power In	+24VDC	BROWN
	2	NPN	Sinking Signal	WHITE
	3	GND	Ground	BLUE
	4	PNP	Sourcing Signal	BLACK
	5	Intensity Control	1-10VDC	GREY

* Some cables use green with yellow stripe for 1-10V adjustment.

Wiring configuration for **OverDrive** operation

	Pin	Function	Signal	Wire Color
	1	Power In	+24VDC	BROWN
	2	NPN	Sinking Signal	WHITE
	3	GND	Ground	BLUE
	4	PNP	Sourcing Signal	BLACK
	5	OverDrive Signal	Ground	GREY


*Analog intensity control is disabled in OverDrive Mode. Light operates at maximum pulse intensity.



optical performance


LE300-XXX

Working Distance mm (inches)	Pattern (80%-100% measured intensity) mm (Inches)
.5m (19.7")	210mm(~8") H x 100mm(~4") V
1m (~59")	270mm(~10.6") H x 255mm(~10") V
Typical output performance	
Distance = .5 meter	
Illumination measurement taken on White Lights – 6500K	
Illumination (Lux)	
Constant ON	OverDrive
8800 lux	44000 lux




LE300-XXX-W

Working Distance mm (inches)	Pattern (80%-100% measured intensity) mm (Inches)
.5m (19.7")	220mm(~9") H x 160mm(~6") V
1m (39.4")	460mm(~18") H x 420mm(~16.5") V
1.5m (59")	570mm(~22") H x 550mm(~22") V
Typical output performance	
Distance = .5 meter	
Illumination measurement taken on White Lights – 6500K	
Illumination (Lux)	
Constant ON	OverDrive
5200 lux	26000 lux



LE300-XXX-L

Working Distance mm (inches)	Pattern (80%-100% measured intensity) mm (Inches)
.5m (19.7")	330mm(~13") H x 50mm(~2") V
1m (39.4")	660mm(~26") H x 100mm(~4") V
1.5m (59")	990mm(~39") H x 150mm(6") V
Typical output performance	
Distance = .5 meter	
Illumination measurement taken on White Lights – 6500K	
Illumination (Lux)	
Constant ON	OverDrive
6800 lux	34000 lux



mounting options



T-slot channel on the back for mounting



According to IEC 62471:2006. Full documentation upon request.

Notice

Exempt Group: No photobiological hazard to eyes or skin even for continuous, unrestricted use.
Applicable for wavelengths: 625, 850, and 940.

Caution

Risk Group 1: Possibly hazardous optical radiation emitted from this product. Do not stare at operating lamp. May be harmful to eye. Safe for most applications except prolonged exposures.
Applicable for wavelengths: 470, 505, 530, and WHI.