

918S Alarm with 924 Adjustable Level Sensor

NEW PRODUCT ANNOUNCEMENT

This adjustable float activated simple switch device with alarm is used to monitor liquid level at a desired set point.

Application

- · Level sensor in liquid storage tanks
- · Activates audible alarm

Features and Details

Alarm Box

- · Audible and visual indicators
- · Self-powered by long-life replaceable lithium batteries
- · Low battery visual indicator
- Audible alarm sounds 90 dB alarm at four feet away
- · Corrosion-resistant and water-resistant housing for long life
- In compliance with UL 913 and CSA 157 intrinsic safety standards for Class I, Division 1 and 2, Group D hazardous location

Sensor

- · Four sensor length ranges
- Fully adjustable within the sensor range length
- · Installs into a 2" female threaded opening
- Normally open switch easily converted to normally closed operation

Materials of Construction

- · Alarm box... polycarbonate plastic
- Wires... Teflon® jacketed wires
- · Floats... 316 stainless steel
- Tube... brass (924); 304 stainless steel (924S)
- Bushing... e-coated steel (924); 304 stainless steel (924S)

Electrical - Level Sensor

• 100 watt resistive load, 300VAC/350VDC max, 1.0A max, SPST

I.D. Number	Description	Weight (lbs)	List Price
918S92406 AK	6" Brass adjustable level sensor with alarm	4.80	\$640.00
918S92412 AK	12" Brass adjustable level sensor with alarm	5.10	\$660.00
918S92420 AK	20" Brass adjustable level sensor with alarm	5.70	\$680.00
918S92430 AK	30" Brass adjustable level sensor with alarm	5.90	\$700.00
918S924S06 AK	6" Stainless steel adjustable level sensor with alarm	4.70	\$770.00
9100924000 AIX	o Stairiless steel adjustable level sellsof with dialiff	4.70	Ψ110.00
918S924S12 AK	12" Stainless steel adjustable level sensor with alarm	5.00	\$790.00
918S924S20 AK	20" Stainless steel adjustable level sensor with alarm	5.50	\$810.00
918S924S30 AK	30" Stainless steel adjustable level sensor with alarm	5.70	\$830.00







570 E. 7th Street, P.O. Box 238 | Dubuque, IA 52004-0238 t. 563.583.5701 | 800.553.4840 | f. 563.583.5028