



1626 Bridgewater Road  
Bensalem, PA 19020  
Toll Free: 800-331-1373  
Fax: 215-245-8554  
[www.prestotape.com](http://www.prestotape.com)

## Technical Data Sheet

### 7176 Low Tack Paper Application Tape

---

#### Product Description:

An economically priced, standard weight saturated blue paper with low tack adhesive is release coated for easier unwind. The product is used for the clean pick-up and transfer of lettering and graphics. It is wrinkle free and leaves no residue or oil. The 7176 is recommended for use with digital and ink jet graphics. The 7176 provides excellent adhesion for transfer of medium to large letters and graphics to their target source for installation and offers a simple release after use.

#### Product Properties / Characteristics:

#### Nominal Results

**Thickness:**  
PSTC 33

**4.0-4.5 mils**

**Adhesion to Steel:**  
PSTC I (oz/in)

**8.0**

**Tack Level:**

**Low**

**Elongation (%):**  
PSTC 31

**3-4**

**Tear Resistance**  
(grams)

**40**

---

The values listed above are averages determined by standard production testing procedures. The suitability for use shall be determined by the user for the particular application.

**Limitations of Warranty:** Presto Tape and seller warrants to customers that coated products constructed and delivered by Presto Tape and seller to be free of defects in workmanship and to meet the specifications published by Presto Tape which are available upon request. for a period of six (6) months from date of delivery and in the event of Presto Tape brand product proved to be defective, the excluding solution, at Presto Tape's option, shall be a) refund the purchase price b) repair or c) replace the defective product. No acceptance or responsibility for loss, or expense, implied or otherwise, shall be assumed by seller or manufacturer. User assumes all risk and liability in connection herewith.

This stated Warranty & Limitation of Liability can only be changed through a written agreement by an authorized officer of Presto Tape.