



SIGNWIRE spec 984184

PAIGE PLUS II

PAIGE PLUS II LED CABLE RGB, P/N 984184 18/4C

LED CABLE RGB

4 CONDUCTOR, 18 AWG PLTC 105°C



PAIGE PLUS LED CABLE

CMG C(UL)US FT-4



Type: This cable consists of 4 conductor 18 AWG stranded tinned copper conductor insulated with Polyvinyl Chloride and a Polyvinyl Chloride jacket overall. Type PLTC, RoHS Compliant

1.0 USE:

A 4 conductor 18 AWG PLTC cable for the use with Class 2, multiple color LED modules (3 max.) and other applications requiring a 4 conductor 18 AWG low voltage PLTC Cable. Red, Green, Blue and Black insulators allow easy circuit connections. Can be used indoors or outdoors.

2.0 CONSTRUCTION

2.1 Conductor:

- 2.1.1 Material: Tinned Copper
- 2.1.2 Size: 18 AWG
- 2.1.3 Construction: Stranded

2.2 Insulation:

- 2.2.1 Material: Polyvinyl Chloride
- 2.2.2 Wall Thickness: .016"
- 2.2.3 O.D.: .075" nom.
- 2.2.4 Color Code: Black, Red, Green and Blue

2.3 Cabling Overall Lay:

- 2.3.1 2 1/2" left hand lay

2.4 Nominal Cabling Diameter:

- 2.4.1 .181"

2.5 Final Jacket:

- 2.5.1 Material: Sunlight Resistant Direct Burial Polyvinyl Chloride
- 2.5.2 Wall Thickness: .035" nom.
- 2.5.3 O.D.: .251" nom.
- 2.5.4 Marking: "PAIGE PLUS II LED CABLE RGB, P/N 984184 18/4C E191596 (UL) CMG C(UL)US FT4 OR (UL) PLTC 105°C SUNLIGHT RESISTANT "ROHS COMPLIANT" SUITABLE FOR WET LOCATIONS OR OUTDOOR USE. WWW.PAIGEELECTRIC.COM"
- 2.5.5 Color: Black

2.6 Temperature / Voltage:

- 2.6.1 105°C / 300V

2.7 Packaging:

- 2.7.1 250 ft. 1 Pac Boxes and 1000 ft. reels